

## TOTEM Series



Screen Size: 640mm \* 1920mm / 1280mm \* 1920mm

Cabinet Weight: 25kg (Standard Dimension)

Pixel Pitch: 1.25mm / 1.538mm / 1.86mm / 2mm / 2.5mm

Module Size: 320mm \* 160mm

## Features

- Available in single-sided or double-sided options
- Flexible installation, adapting to multi-scenario needs
- High contrast ratio with vivid and rich colors
- Supports stacking and hoisting
- Supports remote centralized control

## APPLICATION



Auto Show

Clothing Store

Mall Billboard



Ultra-thin cabinet, 35.6mm thick, uses invisible hinges/rotating latches, neater high-end appearance



Supports single-fold, horizontal-fold, and triple-fold poster screens



High brightness and contrast, with richer and more vivid colors



LED screens with an extremely wide viewing angle have a very broad viewing range, typically reaching 140-160 degrees

| Item                      | P1.25                              | P1.538                     | P1.86                      | P2                         | P2.5                       |
|---------------------------|------------------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| Pixel Pitch               | 1.25mm                             | 1.538mm                    | 1.86mm                     | 2mm                        | 2.5mm                      |
| LED Type                  | SMD1010                            | SMD1212                    | SMD1515                    | SMD1515                    | SMD1515                    |
| Pixel Density             | 640,000dots/m <sup>2</sup>         | 422,750dots/m <sup>2</sup> | 284,444dots/m <sup>2</sup> | 250,000dots/m <sup>2</sup> | 160,000dots/m <sup>2</sup> |
| Module Size               | 320mm(W) * 160mm(H)                | 320mm(W) * 160mm(H)        | 320mm(W) * 160mm(H)        | 320mm(W) * 160mm(H)        | 320mm(W) * 160mm(H)        |
| Module Resolution         | 256dots * 128dots                  | 208dots * 104dots          | 172dots * 86dots           | 160dots * 80dots           | 128dots * 64dots           |
| Driving Mode              | 1/64scan                           | 1/52scan                   | 1/43scan                   | 1/40scan                   | 1/32scan                   |
| Cabinet Resolution        | 512dots * 1,536dots                | 416dots * 1,248dots        | 344dots * 1,032dots        | 320dots * 960dots          | 256dots * 768dots          |
| Cabinet Size              | 640mm * 1,920mm or 1,280 * 1,920mm |                            |                            |                            |                            |
| Cabinet Weight            | 55kg                               |                            |                            |                            |                            |
| Brightness                | 600nits                            | 600nits                    | 800nits                    | 800nits                    | 800nits                    |
| Refresh Rate              | 3,840Hz                            | 3,840Hz                    | 3,840Hz                    | 3,840Hz                    | 3,840Hz                    |
| Gray Scale                | 14bits                             | 14bits                     | 14bits                     | 14bits                     | 14bits                     |
| Maximum Power Consumption | 680W/m <sup>2</sup>                | 680W/m <sup>2</sup>        | 680W/m <sup>2</sup>        | 680W/m <sup>2</sup>        | 1,000W/m <sup>2</sup>      |
| Average Power Consumption | 230W/m <sup>2</sup>                | 230W/m <sup>2</sup>        | 230W/m <sup>2</sup>        | 230W/m <sup>2</sup>        | 300W/m <sup>2</sup>        |
| Certificate               | CE, FCC, ETL, CB                   | CE, FCC, ETL, CB           | CE, FCC, ETL, CB           | CE, FCC, ETL, CB           | CE, FCC, ETL, CB           |